

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS .						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		
1		BECAUSE OF DIFFERENT ENGRAVINGS CREATED -18 RECEIVER TO REPLACE -07 ON TOOL RBW6205G 19432-3G. ADDED ENGRAVING NOTES TO -07 & -18. ADDED -3G TO ALL PART NUMBERS. TO -27 ADDED REF. DIMENSIONS. ON -3 & -17 DRAW BOLTS CHANGED ENGRAVING FROM T/N, S/N, ECT. TO T/N ONLY.	9/21/09	WP	RW		
2	15-0103	-1 DELETED ENGRAVE NOTE7 DELETED FINISH WAS CLEAR ANODIZE.	5/12/15	RJC	JAG		
3	15-0293	-3 CH'D ANGLE WAS 82° IS 90°, ADDED PART MARK FOR PAIRS NOTE.	9/10/2015	RJC	JAG		





NOTES:


1. ORIGINAL No. TO REF:
RBW6205G19232 KIT No. = 3G6205G19232
RBW6205G19232-1 ASSY = 3G6205G19332
RBW6205G19232-3 = 3G6205G19552
RBW6205G19232-7 = 3G6205G19751
2. ALSO SOLD WITH KIT RBW6205G19232-3G.



TITLE

M/R SCISSOR BUSHING REMOVAL TOOL


ASSY	ASSY QTY	B/O	Part #	UNIT	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	RBW6205G19332-3G			-3G REV 3
QII	QII			QIII						MAT'L	DRAWN BY:	PERRITT
			-1	1	DRAW BOLT	4140/4142 Q&T		2		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		D Weil
			-3	2	CLAMP	4140/4142 Q&T		3		.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT FINISH	
			-5	1	RECEIVER	6061		4		.XX ± .01 ANGLES ±.5° 1. BREAK ALL SHARP EDGES .015 x 4		
			-7	1	TALL NUT	BRONZE ALLOY 642		5		OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER	US	ED ON MODEL
		B/O	-9	1	THRUST BEARING		5/64 X Ø9/16 ID X Ø1 OD (APPLID INDUSTRIAL #NTA-916)	1		PLATING	•	AW139
		B/O	-11	2	THRUST WASHER		1/32 X Ø9/16 ID X Ø1 OD (APPLIED INDUSTRIAL #TRA-916	5) 1		SCALE 1:3	7/8/2009	SHEET 1 OF 5





This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	
3	15-0293	-3 CH'D ANGLE WAS 82° IS 90°, ADDED PART MARK FOR PAIRS NOTE.	9/10/2015	RJC	JAG	











M/R SCISSOR BUSHING REMOVAL TOOL

RBW6205G19332-3G-3

MAT'L 4140/4142 Q&T DRAWN BY: UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES APPROVED SIXX ± .005 FRACTIONS ± 1/8 FINISH XX ± .01 ANGLES ± .5° FINISH SPEC

USED ON MODEL

1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
2. DIMENSIONAL LIMITS APPLY AFTER PLATING

AW139

SCALE 1:1


7/8/2009

SHEET 3 OF 5

PERRITT


YELLOW ZINC


CLAMP




This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	
2	15-0103	-7 DELETED FINISH WAS CLEAR ANODIZE.	5/12/15	RJC	JAG	







DART
AEROSPACE

M/R SCISSOR BUSHING REMOVAL TOOL

DWG NO.

SCALE

RBW6205G19332-3G-7

REV

MAT'L BRONZE ALLOY 642 DRAWN BY: UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES XXX ± .005 FRACTIONS ± 1/8 TREAT XX ± .01 ANGLES ± .5° FINISH X ± .1 SPEC

1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
2. DIMENSIONAL LIMITS APPLY AFTER PLATING

1:1

USED ON MODEL AW139

TALL NUT

7/8/2009

SHEET 5 OF 5

PERRITT